

PART NUMBERING SYSTEM SERIES 1, 2 and 3 GAUGES

2 **0** **1** **L** — **2** **5** **4** **E**

TYPE SERIES

- 1** = Steel Case with Chrome Ring. Brass Internals
- 2** = Stainless Steel Case. Brass Internals
- 3** = Stainless Steel Case. 316 SS Internals

SPECIAL FEATURES

- 0** = Standard Gauge
- 1** = removable Ring, Adjustable Pointer

MOUNTING STYLE

- 1** = Bottom Connection / Stem Mounted
- 2** = Back Connection / Stem Mounted
- 3** = Back Connection / U-Clamp, Panel Mount
- 4** = Back Connection / Front Flanged, Panel Mount

FILL TYPE

- D** = Dry - Not Filled
- L** = Glycerin Filled

DIAL SIZE

- 15** = 1½" Diameter
- 20** = 2" Diameter
- 25** = 2½" Diameter
- 35** = 3½" Diameter
- 40** = 4" Diameter

CONNECTION SIZE

- 8** = 1/8" NPT Male
- 4** = 1/4" NPT Male

DIAL RANGE

- A** = 30"-0"hg VAC
- CB** = 30"-0-15 PSI
- CC** = 30"-0-30 PSI
- CD** = 30"-0-60 PSI
- CE** = 30"-0-100 PSI
- CF** = 30"-0-150 PSI
- CH** = 30"-0-300 PSI
- B** = 0-15 PSI
- C** = 0-30 PSI
- D** = 0-60 PSI
- E** = 0-100 PSI
- F** = 0-160 PSI
- G** = 0-200 PSI
- H** = 0-300 PSI
- I** = 0-400 PSI
- J** = 0-500 PSI
- K** = 0-600 PSI
- L** = 0-800 PSI
- M** = 0-1000 PSI
- N** = 0-1500 PSI
- O** = 0-2000 PSI
- P** = 0-3000 PSI
- Q** = 0-4000 PSI
- R** = 0-5000 PSI
- S** = 0-6000 PSI
- U** = 0-10,000 PSI

EXAMPLE - 201L-254E

- 2** = Stainless Steel Case. Brass Internals
- 0** = Standard Gauge
- 1** = Bottom Connection / Stem Mounted
- L** = Glycerin Filled
- 25** = 2½" Diameter
- 4** = 1/4" NPT Male
- E** = 0-100 psi